

F7K series Thermal-Links/Resistor Assemblies

F7K系列 溫度保險絲附電阻器




- Thermal-Links/Resistor Assemblies is a product that combined with thermal-links of fusible alloy type and 7W wire wound resistor type.
- F7K is RoHS compliance product, non-Pb and non-Cd contains.
- F7K got excellent interception characteristic when abnormality overload happened.
- Especially, F7K adopted excellent characteristic resistive element against the In-rush current, and it is the best for preventing In-rush current.

- 可熔合金型溫度保險絲和 7W 卷線電阻器組合成一體的製品。
- F7K 是不含鉛、鎘的製品。(RoHS 對象製品)
- F7K 能在超負荷等異常時，發揮它的優越切斷特性。
- 特別地採用了對突入電流有優越性能的電阻元素，最適合防止突入電流。




- ✓ Approved by UL/C-UL, TUV
- ✓ 已通過認證: UL/C-UL, TUV

Dimension 尺寸



Construction 構造圖



Models Component 型號構成


F7K **J**

Series 系列名 Nominal resistance value 額定電阻值 Resistance tolerance 電阻值容許偏差 Thermal-Links 溫度保險絲


J: ±5% **13:** Tf 136°C **14:** Tf 145°C

Ratings 額定

Model Name 型號	Rated power 額定電力 (25°C)	Nominal resistance value 額定電阻值	Resistance tolerance 電阻值容許偏差	Thermal-Links 溫度保險絲				UL C-UL	TUV
				Model Name 型號	Rated functioning temp. 額定動作溫度 (Tf)	Rated voltage 額定電壓	Rated current 額定電流		
F7K □ □ □ J13	3.0W	1.8~820Ω	± 5%	LSF	136°C	AC250V	5A	○	○
F7K □ □ □ J14	3.5W	1.8~820Ω		L7F	145°C	AC250V	5A	○	○





Derating Curve 降低負荷曲線



Interception Characteristics 切斷特性

Interception Time vs. Wattage 切斷性能



Performance 其他性能

Test Characteristics 切斷時間 (秒以內)	Test Methods 試驗方法		Specifications 規格									
Resistance value 電阻值	The following DC voltage is applied across lead terminals for measurements. 導線端子間施加下表的直流電壓進行測定。 <table><tr><th colspan="2">Nominal resistance range 額定電阻值範圍</th><th>Max. applied Voltage 最高承受電壓</th></tr><tr><td>1 and over 1 以上</td><td>less than 10 10 未滿</td><td>0.3</td></tr><tr><td>10 and over 10 以上</td><td>less than 100 100 未滿</td><td>1</td></tr></table>		Nominal resistance range 額定電阻值範圍		Max. applied Voltage 最高承受電壓	1 and over 1 以上	less than 10 10 未滿	0.3	10 and over 10 以上	less than 100 100 未滿	1	Resistance shall be within ±5% of nominal resistance value. 在±5%以內
Nominal resistance range 額定電阻值範圍		Max. applied Voltage 最高承受電壓										
1 and over 1 以上	less than 10 10 未滿	0.3										
10 and over 10 以上	less than 100 100 未滿	1										
Functioning temperature 動作溫度	Soaking the product in the oil bath of temperature rising at 0.5/per min. Then measure the temperature of oil. The measure beginning temperature is -20°C of rated functioning temperature, and the detection current is assumed to be 10mA or less. 製品在每分鐘 0.5°C 的油槽中，製品動作時由槽內溫度的測定。 測定開始定額溫度為 -20°C，檢測電流在 10mA 以下。		F7K□□□J13: 136+0-7°C F7K□□□J14: 145+0-7°C									
Insulation resistance 絕緣電阻	Between body and lead terminals 主體、導線端子間	DC500V is impressed and measured between metallic foil wrapped on the case, and lead terminals. 在水泥殼上的金屬箔與導線端子間施加 DC500V 進行測定。	Insulation resistance shall be 1000MΩ or above. 在 1000MΩ以上									
	Between body lead terminals 兩根導線端子間	DC500V is impressed for and measured between lead terminals after functioning temperature test. 動作溫度試驗後，導線端子間施加 DC500V 進行測定。	Insulation resistance shall be 0.2MΩ or above. 在 0.2MΩ以上									
Dielectric strength 耐電壓	Between body and lead terminals 主體、導線端子間	AC1.5kV is impressed for 1 minute and measured between metallic foil wrapped on the case, and lead terminals. (Cutoff current 0.5mA) 在水泥殼上的金屬箔與導線端子間施加 AC1.5kV 進行 1 分鐘測定。(檢測電流 0.5mA)	The products shall withstand for 1 minute. 能承受 1 分鐘									
	Between body lead terminals 兩根導線端子間	AC500V is impressed for 1 minute and measured between lead terminals after functioning temperature test. (Cutoff current 0.5mA) 動作溫度試驗後，導線端子間施加 AC500V 進行 1 分鐘測定。(檢測電流 0.5mA)	The products shall withstand for 1minute. 能承受 1 分鐘									
Temperature coefficient of resistance 電阻溫度系數	Room temperature / 70°C up 室溫 / 70°C 以上		±250ppm/°C									
Short time overload 短時間過負荷	Rated power x 10, for 5 sec. 額定電力×10 倍，承受 5 秒鐘		±(2%+0.05Ω)									
Soldering heatproof 焊接耐熱性	265°C± 5°C, 10 sec.		±(1%+0.05Ω)									
Terminal strength 端子強度	Pull: 20N, 1 min. Bending: 90°C, 1 cycle 拉力: 20N，1 分鐘 扭曲: 90°C，1 週期		No mechanical damages 無斷線、鬆動、破損									
Humidity resistance 耐濕性	40°C, Humidity 90~95%RH, 10000 hours 40°C，濕度 90~95%RH，10000 小時		±(2%+0.05Ω)									
Load life 負荷壽命特性	Rating load 1000 hours, 1.5 hours ON / 0.5 hours OFF cycle 額定負荷 1000 小時，1.5 小時開/0.5 小時關的週期		±(3%+0.05Ω)									