


VG Series Products

Mass Interconnect Technologies



VGRCB-13CPF

VGFCB-13CPF

VGRCB-13CPF

VGFCB-13CPF

The VGRCB-13CPF provides 13 contacts for coax, power or a combination of both contact styles. Coax contacts are provided for signals up to 500 Mhz and power signals up to 30 Amps / 250 VAC. Proper alignment is ensured by two precision alignment pins per block. Two shoulder mounting screws per VGR block allow the block to float in the receiver. Contacts, blocks and cables sold separately.

Coax Contact Pair Specifications

Voltage	250VAC
Current	1.5 Amps
Contact Resistance	6mΩ
Capacitance	5pf
Inductance	3nH
Bandwidth (-3db roll off)	500 Mhz
Durability	25,000 cycles
Coax Connection Type	Crimp

Power Contact Pair Specifications

Power Contact.....	30 Amps
--------------------	---------

Ordering Information

Receiver

Receiver Module.....	VGRCB-13CPF
36" Receiver Coax Cable Assy.....	CR-CA50RG174-36
Receiver Power Contact.....	CR-610116102

Accessories

Receiver Contact Extraction Tool	VGRXT
--	-------

Fixture

Fixture Module	VGFCB-13CPF
36" Fixture Coax Cable Assy.....	CF-CA50RG174-36
10 AWG Fixture Power Contact	CF-610115102
12 AWG Fixture Power Contact	CF-610115103

Fixture Contact Extract Tool	VGFXT
------------------------------------	-------

